

Date: 1/1/2015

Solder Alloy Sac305 (Acid/Rosin/No Clean Core Wire)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Solder Alloy Sac305 Acid/Rosin/No Clean Core (Sn96.5Ag3Cu0.5)

MANUFACTURER: Amerway Inc.

ADDRESS: 3701 Beale Ave.

Altoona, PA 16601

PHONE: 814-944-0200

FAX PHONE: 814-944-1463

PRODUCT USE: Solder PREPARED BY: Terry Buck

CHEMTREC: 800-424-9300

CHEMTREC (Outside US & Canada): 703-527-3887

SECTION 1 NOTES:

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

ROUTES OF ENTRY:

EYES: Dust or fumes will be irritant.

SKIN: Not a route of entry into the body. May cause an allergic skin reaction.

INGESTION: Harmful if swallowed. If swallowed, call a poison Control Center or doctor/physicisn if you feel unwell.

INHALATION: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

If breathing is difficult, move victim to fresh air.

NFPA RATINGS (scale 0-4)

Health= 1
Fire= 1
Reactivity= 0

HMIS RATINGS (scale 0-4)

Health= 1 Fire= 1 Reactivity= 0

SECTION 2 NOTES: May cause damage to organs through prolonged or repeated exposure.

Suspected of damaging fertility or the unborn child. May cause long lasting harmful effects to aquatic life.



Date: 1/1/2015

Solder Alloy Sac305 (Acid/Rosin/No Clean Core Wire)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT: Tin/Lead

 CAS NO.
 % WT
 % VOL
 SARA 313 REPORTABLE

 7440-31-5 Tin (Sn)
 95-97
 Yes

 7440-22-04 Silver (Ag)
 3-4
 Yes

 7440-50-8 Copper (Cu)
 0-1
 * Trade Secret
 0-3

ACGIH TLV-TWA: Tin 2mg/cu ACGIH

2mg/cu m (inorganic) OSHA 0/1mg/cu m (organic) OSHA

Silver 0.1 mg/cu m ACGISH/OSHA

Copper 0.1 mg/cu m ACGIH/OSHA

SECTION 3 NOTES: Composition and percent of solder alloys varies widely and can be determined by product label.

This product does not contain any Substance of Very High Concern (SVHC) on the European Chemicals Agency

(ECHA) candidate list.

SECTION 4: FIRST AID MEASURES

EYES: Rinse opened eye for several minutes under running water.

SKIN: Immediately wash with soap and water and rinse thoroughly.

INGESTION: Seek immediate medical advice.

INHALATION: Supply fresh air, seek medical attention.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 4 NOTES:

SECTION 5: FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Suitable extinguishing agents – CO2, sand, extinguishing powder. Do not use water.

SPECIAL FIRE FIGHTING PROCEDURES: If metal is present where there is fire, wear self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: In case of fire the following can be released:

Carbon monoxide (CO) Nitrogen oxides (NOx) Carbon dioxide (CO2)

HAZARDOUS DECOMPOSITION PRODUCTS: Lead fumes at high temperatures (above 800 degrees F.)

SECTION 5 NOTES:

^{*} Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Date: 1/1/2015

Solder Alloy Sac305 (Acid/Rosin/No Clean Core Wire)

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES:

Ensure adequate ventilation

Do not allow to enter sewers/surface or ground water.

Allow to solidify and collect in sealed containers for disposal.

Use caution to avoid breathing fumes if a gas torch is used to cut up large pieces.

SECTION 6 NOTES:

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE:

Store in dry conditions. Ensure adequate ventilation.

OTHER PRECAUTIONS:

If fume or dust is being generated, mechanical ventilation must be provided to maintain exposure level below TLV,s

SECTION 7 NOTES:

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

VENTILATION: If fume or dust is being generated, mechanical ventilation must be provided to maintain exposure level below TLV,s

RESPIRATORY PROTECTION: Respiratory protection is recommended but only if TLV's are exceeded. Use a NIOSH?MSHA approved respirator for toxic dust and/or fume.

EYE PROTECTION: Wear safety glasses during soldering operations.

SKIN PROTECTION: Skin protection is not normally needed but wash hands thoroughly.

CONTROL PARAMETERS:

7440-31-5 TIN (Sn)

PEL - Long term value: 2 mg/m3

metal

REL - Long term value: 2 mg/m3

TLV - long term value: 2 mg/m3

metal

MERWAYING.

SAFETY DATA SHEET (SDS)

Date: 1/1/2015

Solder Alloy Sac305 (Acid/Rosin/No Clean Core Wire)

7440-22-4 Silver (Ag)

PEL - Long term value: 0.01 mg/m3

REL - Long term value: 0.01 mg/m3

TLV - long term value: 0.1 mg/m3

metal: dust and fume

8050-09-7 Rosin

TLV - (SEN); L NIC_DSEN< RSEN

SECTION 8 NOTES:

PEL= Permissible Exposure Limit (OSHA)
TLV= Threshold Limit Value (ACGIH)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Silver grey.

ODOR: Odorless

PHYSICAL STATE: Solid

pH VALUE: Not applicable

MELTING POINT/MELTING RANGE: 217 *C (423 *F)

VAPOR PRESSURE (mmHg): Not applicable

VAPOR DENSITY: Not applicable

WATER SOLUBILITY: Insoluble

SOLVENT CONTENT: Organic solvents = 0/0%

Solid Content = 100.0%

SECTION 9 NOTES:

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): Not applicable

INCOMPATIBILITY (MATERIAL TO AVOID): Strong acids, oxidizers, reducing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: No decomposition if used according to specifications.

HAZARDOUS POLYMERIZATION: Will not occur



Date: 1/1/2015

Solder Alloy Sac305 (Acid/Rosin/No Clean Core Wire)

SECTION 10 NOTES:

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Skin Contact: Irritant to skin and mucous membranes.

Eye: Dust or fume will be irritant.

Ingestion: May cause gastrointestinal irritation.

Inhalation: Inhalation of dust and fumes must be avoided. Flux fumes during soldering may cause damage of mucous membranes

and respiratory system.

SECTION 11 NOTES:

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:

Aquatic toxicity: No further relevant information available.

Note: Do no allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 12 NOTES:

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Must not be disposed of together with household garbage. Do not allow to reach sewage system. Disposal must be made according to official regulations. If proper disposal methods are not available, return product to supplier for reprocessing.

SECTION 13 NOTES:

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION
PROPER SHIPPING NAME: Not regulated
HAZARD CLASS: Not regulated
ID NUMBER: Not regulated
PACKING GROUP: Not regulated

LABEL STATEMENT: Not regulated

WATER TRANSPORTATION

PROPER SHIPPING NAME: Not regulated

HAZARD CLASS: Not regulated ID NUMBER: Not regulated PACKING GROUP: Not regulated LABEL STATEMENTS: Not regulated



Date: 1/1/2015

Solder Alloy Sac305 (Acid/Rosin/No Clean Core Wire)

AIR TRANSPORTATION

PROPER SHIPPING NAME: Not regulated HAZARD CLASS: Not regulated

ID NUMBER: Not regulated
PACKING GROUP: Not regulated
LABEL STATEMENTS: Not regulated

OTHER AGENCIES:

SECTION 14 NOTES:

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT): All components listed for the subject finished product are on the TSCA Inventory of Chemical Substances and are not subject to any chemical specific regulation under TSAC Section 12(b) export notification requirements delineated at 40 CFR part 707, subpart D.

All ingredients are listed or exempt from listing.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

313 REPORTABLE INGREDIENTS: 7439-92-1 LEAD (Pb)

STATE REGULATIONS: California Proposition 65/Chemicals known to cause cancer. None of the ingredients listed.

California Proposition 65/Chemicals known to cause reproductive toxicity, None of the ingredients listed.

INTERNATIONAL REGULATIONS:

SECTION 15 NOTES:

SECTION 16: OTHER INFORMATION

OTHER INFORMATION: This information is given in good faith, no warranty, express or implied is made. Amerway Inc. makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchasers use. The data on this Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employes must be trained on how to use a Safety Data Sheet as a source for hazard information.

PREPARATION INFORMATION: Contact: tbuck@amerway.com